

Specification Sheets

PRODUCT NAME:	Lexgard® MP 1000
PRODUCT CODE:	MP 1000
PERFORMANCE TESTING:	<p>Forced Entry: ASTM F1233 Class V HP White Level IV- TP-0500.02 WMFL Level II</p> <p>Ballistic: UL Standard 752- Level 2 .357 Magnum Jacketed Lead Soft Point No Spall, No Penetration</p>
CONSTRUCTION:	<p>1/8" Polycarbonate (Abrasion resistant) Urethane Interlayer 3/8" Polycarbonate Urethane Interlayer 3/8" Polycarbonate Urethane Interlayer 1/8" Polycarbonate (Abrasion resistant)</p>
THICKNESS:	1" Nominal (1.00")
THICKNESS TOLERANCE:	.948" /1.18"
WEIGHT:	6.40 Lbs. / Square Foot
SIZE:	<p>72" x 96" Maximum 12" x 12" Minimum for UL Ballistic Rating</p>
OPTIONS:	Bronze, Gray, Green, Tint
TECHNICAL DATA:	<p>U-Value- .62 Shading Co-efficient- .93 Light Transmission- .72</p>
APPLICABLE STANDARDS:	<p>ANSI Z97.1 CPSC 16 CFR 1201 (Category I and II) ASTM C 1036 ASTM C 1172</p>
SINGLE RESPONSIBILITY:	Standard Bent Glass products are covered by our Single Responsibility® Program that ensures one firm has handled and is accountable for all phases of manufacturing.
INSTALLATION:	<p>When used for ballistic protection, glazing should be installed in a UL Level 2 Bullet Resistant frame system. Holes must be covered with a UL listed device. All glass should be installed in accordance with the guidelines set forth in the current edition of the Glass Association of North America (GANA) Glazing and Sealant Manuals. Glazing systems should incorporate a weep system to allow moisture and water to escape the glazing channel.</p> <p>Recommended Clearance: Face: 1/8" per side Edge: 1/4" Bite: 1"</p>