

Specification Sheets

PRODUCT NAME:	Lexgard® MP 750
PRODUCT CODE:	MP 750
PERFORMANCE TESTING:	Ballistic: UL Standard 752- Level 1 9mm Full Metal Copper Jacket with Lead Core No Spall, No Penetration
CONSTRUCTION:	1/8" Polycarbonate (Abrasion resistant) Urethane Interlayer 1/2" Acrylic Urethane Interlayer 1/8" Polycarbonate (Abrasion resistant)
THICKNESS:	3/4" Nominal (.75")
THICKNESS TOLERANCE:	.69" / .81"
WEIGHT:	4.60 Lbs. / Square Foot
SIZE:	72" x 96" Maximum 12" x 12" Minimum
OPTIONS:	Bronze, Gray, Green
TECHNICAL DATA:	U-Value- .71 Shading Co-efficient- 1.04 Light Transmission- .87
SINGLE RESPONSIBILITY:	Standard Bent Glass products are covered by our Single Responsibility® Program that ensures one firm has handled and is accountable for all phases of manufacturing.
INSTALLATION:	Glazing must be installed in a UL Level 1 Bullet Resistant frame system. Holes must be covered with a UL listed device. All glazing should be installed in accordance with the guidelines set forth in the current edition of the Glass Association of North America (GANA) Glazing and Sealant Manuals. Glazing systems should incorporate a weep system to allow moisture and water to escape the glazing channel. Recommended Clearance: Face: 1/8" per side Edge: 3/8" Bite: 1"